



H05Z1-U / H07Z1-U H07Z1-R



1) Som veya Örgülü Bakır
Solid or Stranded Copper

2) HFFR İzole
HFFR Insulation

Re : Som Yuvarlak İletken
Re : Solid Single Round Conductor
Rm : Çok Tellî Yuvarlak İletken
Rm : Multi Wire Round Conductor



STANDARD

TS EN 50525-3-31

TEKNİK BİLGİLER

İzin verilen işletme sıcaklığı	: 70 °C
Kısa devre sıcaklığı	: 160 °C
Test gerilimi (AC)	: 2 - 2.5 kV
Serim sıcaklığı min	: 5 °C
Anma gerilimi	: 05-300/500V 07-450/750V

KULLANIM ALANLARI

Oteller, okullar, yüksek binalar, hastaneler, bilgi işlem merkezleri ve insanların yoğun olarak bulunduğu iş merkezleri ile yangına hassas bölgelerde kullanılır.

TECHNICAL DATA

Permissible operating temperature	: 70 °C
Short circuit temperature	: 160 °C
Test Voltage (AC)	: 2 - 2.5 kV
Installation temperature minimum	: 5 °C
Rated Voltage	: 05-300/500V 07-450/750V

USAGE AREAS

It is used in hotels, schools, high buildings, hospitals, data processing centers and crowded business centers and fire-sensitive areas.



TEKNİK ÖZELLİKLER

TECHNICAL DATA

H05Z1-U / H07Z1-U

H07Z1-R

H05Z1-U (300/500V)

Nominal Kesit	Kablo Dış Çapı(Yaklaşık)	Akım Taşıma Kapasitesi Havada	İletken DC Direnci (20°C)	Net Ağırlık (Yaklaşık)	Ambalaj miktarı	Ambalaj
Rated Cross-section	Overall Diameter of Cable (Approx)	Current Carrying Capacity in Air	Conductor DC Resistance at 20°C	Net Weight (Approx)	Amount of Packing	Packing
mm ²	mm	A	ohm / km	kg / km	m	C: Kargal/Coil R: Makara/Reel
0.5	2	9	36	8.25	100	C 100
0.75	2.15	15	24.5	10.65	100	C 100
1	2.3	19	18.1	13.26	100	C 100

H07Z1-U (450/750V)

Nominal Kesit	Kablo Dış Çapı(Yaklaşık)	Akım Taşıma Kapasitesi Havada	İletken DC Direnci (20°C)	Net Ağırlık (Yaklaşık)	Ambalaj miktarı	Ambalaj
Rated Cross-section	Overall Diameter of Cable (Approx)	Current Carrying Capacity in Air	Conductor DC Resistance at 20°C	Net Weight (Approx)	Amount of Packing	Packing
mm ²	mm	A	ohm / km	kg / km	m	C: Kargal/Coil R: Makara/Reel
1.5	2.75	24	12.1	19.45	100	C 100
2.5	3.35	32	7.41	30.45	100	C 100
4	3.8	42	4.61	44.65	100	C 100
6	4.3	54	3.08	63.2	100	C 100
10	5.45	73	1.83	104.7	100	C 100

H07Z1-R (450/750V)

Nominal Kesit	Kablo Dış Çapı(Yaklaşık)	Akım Taşıma Kapasitesi Havada	İletken DC Direnci (20°C)	Net Ağırlık (Yaklaşık)	Ambalaj miktarı	Ambalaj
Rated Cross-section	Overall Diameter of Cable (Approx)	Current Carrying Capacity in Air	Conductor DC Resistance at 20°C	Net Weight (Approx)	Amount of Packing	Packing
mm ²	mm	A	ohm / km	kg / km	m	C: Kargal/Coil R: Makara/Reel
1.5	2.95	24	12.1	20.3	100	C 100
2.5	3.6	32	7.41	32.1	100	C 100
4	4.1	42	4.61	46.45	100	C 100
6	4.65	54	3.08	64.9	100	C 100
10	5.9	73	1.83	109.1	100	C 100
16	6.85	98	1.15	163.5	100	C 100
25	8.45	129	0.727	253.9	100	C 100
35	9.55	158	0.524	343.1	1000	R 700
50	11.2	197	0.387	463.8	1000	R 800
70	12.9	245	0.268	660.6	1000	R 800
95	15.1	290	0.193	912.9	1000	R 1000
120	16.25	345	0.153	1132	1000	R 1000
150	18.2	390	0.124	1400	1000	R 1100
185	20.65	445	0.0991	1771	1000	R 1200
240	23.45	525	0.0754	2315	1000	R 1300
300	26.5	605	0.0601	2858	1000	R 1400